





6X12 + 7 GALVANİZLİ	Halat Anma Çapı (mm) Wire Diameter (mm)	Tolerans (%)	Birim Ağırlık (kg/m) Unit Weight (kg/m)	En Küçük Kopma Kuvveti Min. Breaking Load
	6	+5 -0	0,098 0,175 0,273 0,393	1270 2290 3670 5210
8				
10				
12				



1X19 PASLANMAZ ÇELİK HALAT	Halat Anma Çapı (mm) Wire Diameter (mm)	Birim Ağırlık (kg/m) Unit Weight (kg/m)	En Küçük Kopma Kuvveti Min. Breaking Load
	2	0,020	336
3	0,045	756	
4	0,079	1340	
5	0,124	2100	
6	0,178	3030	
8	0,317	5380	
10	0,495	8400	
12	0,713	12100	



7X19 PASLANMAZ ÇELİK HALAT	Halat Anma Çapı (mm) Wire Diameter (mm)	Birim Ağırlık (kg/m) Unit Weight (kg/m)	En Küçük Kopma Kuvveti Min. Breaking Load
	2	0,017	212
3	0,034	477	
4	0,061	849	
5	0,095	1326	
6	0,138	1960	
8	0,243	3400	
10	0,381	5310	
12	0,548	7650	



PVC KAPLI ÇELİK HALAT	Halat Anma Çapı (mm) Wire Diameter (mm)	Halat Cinsi Type of Wire	En Küçük Kopma Kuvveti Min. Breaking Load
	2/3	6x7	250
2/4	6x7	250	
3/5	6x7	550	
4/6	6x7	900	
5/7	6x7	1500	
6/8	6x12+7	2000	
8/10	6x12+7	3600	
10/12	6x12+7	5700	